

Application fields reversible hinge for internal doors mod. TWIN

Sash weight: 12 kg/m<sup>2</sup>

| DIMENSIONS              |             |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |
|-------------------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|
| SRH<br>(height)<br>(mm) | SRW (width) |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |
|                         | 300         | 400 | 500 | 600 | 650 | 700 | 750 | 800 | 850 | 900 | 950 | 1000 | 1050 | 1100 | 1150 | 1200 |
| 1800                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2    | 2    |      |      |      |
| 1900                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2    | 2    |      |      |      |
| 2000                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2    | 2    |      |      |      |
| 2100                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2    | 2    | 2    |      |      |
| 2200                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2    | 2    | 2    |      |      |
| 2300                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2    | 2    | 2    |      |      |
| 2400                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2    | 2    | 2    |      |      |
| 2500                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2    | 2    | 3    |      |      |
| 2600                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2    | 3    | 3    |      |      |
| 2700                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 3    | 3    | 3    |      |      |
| 2800                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 3    | 3    | 3    |      |      |

NB. The application fields are valid even with medium/low consistency wood (for example pine). When the SRW >1800 mm we recommend the use of a third hinge to prevent the bending of the sash also where the application fields provide for two hinges.

Sash weight: 16 kg/m<sup>2</sup>

| DIMENSIONS              |             |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |
|-------------------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|
| SRH<br>(height)<br>(mm) | SRW (width) |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |
|                         | 300         | 400 | 500 | 600 | 650 | 700 | 750 | 800 | 850 | 900 | 950 | 1000 | 1050 | 1100 | 1150 | 1200 |
| 1800                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   |     |      |      |      |      |      |
| 1900                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   |     |      |      |      |      |      |
| 2000                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   |      |      |      |      |      |
| 2100                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   |      |      |      |      |      |
| 2200                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   |     |      |      |      |      |      |
| 2300                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 3   | 3   |      |      |      |      |      |
| 2400                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 3   | 3   | 3   |      |      |      |      |      |
| 2500                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 3   | 3   | 3   | 3   |      |      |      |      |      |
| 2600                    | 2           | 2   | 2   | 2   | 2   | 2   | 2   | 3   | 3   | 3   | 3   |      |      |      |      |      |
| 2700                    | 2           | 2   | 2   | 2   | 2   | 2   | 3   | 2   | 3   | 3   | 3   |      |      |      |      |      |
| 2800                    | 2           | 2   | 2   | 2   | 2   | 2   | 3   | 3   | 3   | 3   | 3   |      |      |      |      |      |

NB. The application fields are valid even with medium/low consistency wood (for example pine). When the SRW >1800 mm we recommend the use of a third hinge to prevent the bending of the sash also where the application fields provide for two hinges.